Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012



Name of the product

Construction Quicklime

Revision Date: January 2025 Version: 2.0/EN

SECTION 1: Identification

Product identifier

Product name

Construction Quicklime

Other names / Synonyms

CQL, Cal 85, Dryox, HiCal QL, Hi Cal Quicklime, Hi Cal Steel Grade, Hi Calcium Pulverized W/FLO Aid, Hi Calcium Quicklime Water Grade, Hot Lime, Lime Fines, Lime, Mini Pebble, P CC Grade-Small Rescreened, PCC Lime Burning, PCC, Pulverized Lime with Flow aid, Quicklime Fines, Rice, Stabilime 50-50, Stabilime Blend 70-30, Stabilime, Steel Grade-Small Rescreened, Steel Grade-Small, Thiosorbic Lime, Water Grade-Small

1.1. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Manufacture of glass, brick, block and other building materials; pH adjustment; flocculation; soil conditioning; soil stabilization; soil modification, soil drying; solidification and dewatering. Restricted to professional users.

Uses advised against

None known.

1.2. Details of the supplier of the safety data sheet

Company and address

Carmeuse Americas

11 Stanwix Street, 21st Floor PA 15222 Pittsburgh USA Phone: (412) 995-5500 Fax: (412) 995-5594 https://www.carmeuse.com/

Contact person

Carmeuse Americas Website: https://www.carmeuse.com/na-en

1.3. Emergency telephone number

Infotrac: (800) 535-5053 (24hr/7days a week) See also section 4 "First aid measures".

SECTION 2: Hazard(s) identification

OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

2.1. Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.

Eye Dam. 1; H318, Causes serious eye damage.

STOT SE 3; H335, May cause respiratory irritation.

Carc. 1A; H350i, May cause cancer by inhalation.

STOT RE 1; H372, Causes damage to organs through prolonged or repeated exposure.

2.2. Label elements





Signal word Danger

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012



Name of the product

Construction Quicklime

Revision Date: January 2025 Version: 2.0/EN

Hazard statement(s)

Causes skin irritation. (H315) Causes serious eye damage. (H318) May cause respiratory irritation. (H335) May cause cancer by inhalation. (H350i) Causes damage to organs through prolonged or repeated exposure. (H372)

Precautionary statement(s)

General

Prevention

Obtain special instructions before use. (P201) Do not breathe dust. (P260)

Wash hands and exposed skin thoroughly after handling. (P264)

Wear eye protection/protective gloves. (P280)

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)

IF exposed or concerned: Get medical advice/attention. (P308+P313)

Immediately call a POISON CENTER/doctor. (P310)

Get medical advice/attention if you feel unwell. (P314)

Storage

Store in a well-ventilated place. Keep container tightly closed. (P403+P233)

Disposal

Dispose of contents/container in accordance with local regulation

(P501)

Additional labelling

Restricted to professional users.

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Calcium oxide	CAS No.: 1305-78-8	>89%	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335	
Silica-crystalline quartz	CAS No.: 14808-60-7	0.1-2.0%	Carc. 1A, H350i STOT RE 1, H372	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

Crystalline Silica is reported as total silica and not just the respirable fraction. There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SECTION 4: First-aid measures

4.1. Description of first aid measures



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012



Name of the product

Construction Quicklime

Revision Date: January 2025 Version: 2.0/EN

General information

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Some metal oxides 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the Poison Help Line on 1-800-222-1222 (24/7) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances. Ensure adequate ventilation, especially in confined areas.

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012



Name of the product

Construction Quicklime

Revision Date: January 2025 Version: 2.0/EN

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Limit spillage, sweep up and shovel into appropriate containers for disposal. Store in suitable, closed containers for disposal.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid direct contact with the product. Avoid contact during pregnancy and while nursing. Smoking, drinking and consumption of food is not allowed in the work area. See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

No special conditions required.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

No specific requirements

Incompatible materials

Water Strong acids reactive fluoridated compounds reactive brominated compounds reactive powdered metals Organic acid anhydrides interhalogen compounds aluminum powder

reactive phosphorous compounds

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Calcium oxide Long term exposure limit (OSHA Table Z-1) (mg/m³): 5 Long term exposure limit (ACGIH TLV) (mg/m³): 2 Long term exposure limit (NIOSH REL) (mg/m³): 2

Silica-crystalline quartz Long term exposure limit (ACGIH TLV) (mg/m³): 0.025 (resp.) for α-quartz and cristobalite Long term exposure limit (NIOSH REL) (mg/m³): Potential occupational carcinogen; 0.05

Part 1910 - Occupational Safety and Health Standards (29 CFR 1910.1000 TABLE Z-1 - Limits for Air Contaminants)

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012



Name of the product

Construction Quicklime

Revision Date: January 2025 Version: 2.0/EN

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Do not recirculate outlet air that contain the substances.

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and showers are clearly marked.

Ensure that eyewash stations and safety showers are located within easy reach.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

- All ventilation systems should be filtered before discharge to atmosphere.
- Avoid releasing to the environment.
- Contain the spillage. Any large spillage into watercourses must be alerted to the regulatory authority.

Individual protection measures, such as personal protective equipment

Generally

Appropriate footwear, additional skin & eye protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory Equipment

Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear an appropriate NIOSH approved respirator if concentration levels exceed the safe exposure limits.

Skin protection

Since calcium oxide is classified as irritating to skin, dermal exposure has to be minimised as far as technically feasible. Protective standard working clothes fully covering skin, full length trousers,

long sleeved overalls, with close fittings at openings and shoes resistant to caustics and avoiding dust penetration are required to be worn.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products. Considering the parameters specified by the glove manufacturer. The time to breakthrough for any glove material may be different per glove manufacturer. In the case of mixtures, the

protection time of the gloves cannot be accurately estimated.

Eye protection

Do not wear contact lenses. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists,

gases or dusts. If contact is possible, the following protection should be worn: chemical splash goggles and/ or face shield.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid Color White to dark Gray Odor None

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012



Name of the product

Construction Quicklime

Revision Date: January 2025 Version: 2.0/EN

```
Odor threshold (ppm)
      Not applicable
  pН
   pH in solution
      12.5 at 25°C (%)
   Density (g/cm<sup>3</sup>)
      3.2-3.4
   Kinematic viscosity
      Not applicable
   Particle characteristics
      Particle size: Variable
Phase changes
   Melting point (°F)
      4658
   Melting point (°C)
      2570
   Boiling point (°F)
      2850
   Boiling point (°C)
      5162
   pressure Not
      applicable
   Relative density Not
      applicable
   Decomposition temperature (°F)
      Not applicable
   Evaporation rate (n-butylacetate = 100)
      Not applicable
Data on fire and explosion hazards
   Flash point (°F)
      Not applicable
   Flammability (°F)
      Not applicable
   Auto-ignition temperature (°F)
      Not applicable
   Explosion limits (% v/v)
      Not applicable
Solubility
   Solubility in water
      1.3376 g/l at 20 °C (68 °F)
      Test method: Regulation (EC) No. 440/2008, Annex, A.6
   n-octanol/water coefficient (LogKow)
      Testing not relevant or not possible due to the nature of the product.
   Solubility in fat (g/L)
      Testing not relevant or not possible due to the nature of the product.
9.2. Other information
   Sensitivity to shock
      No
   Evaporation rate (n-butylacetate = 100)
      Not applicable
   Other physical and chemical parameters
      No data available.
```

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012



Name of the product

Construction Quicklime

Revision Date: January 2025 Version: 2.0/EN

Oxidizing properties Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity No data available. 10.2. Chemical stability The product is stable under the conditions, noted in section 7 "Handling and storage". 10.3. Possibility of hazardous reactions None known. 10.4. Conditions to avoid None known. 10.5. Incompatible materials Water Strong acids reactive fluoridated compounds reactive brominated compounds reactive powdered metals Organic acid anhydrides interhalogen compounds aluminum powder reactive phosphorous compounds 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity Product/substance Calcium oxide Species: Rat Route of exposure: Oral Test: LD50 Result: 3059 mg/kg Product/substance Silica-crystalline quartz Species: Rat Route of exposure: Oral Test⁻ LD50 22500 mg/kg Result: Skin corrosion/irritation Causes skin irritation. Serious eye damage/irritation Causes serious eye damage.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

May cause cancer by inhalation.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012



Name of the product

Construction Quicklime

Revision Date: January 2025 Version: 2.0/EN

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Carcinogenic effects: This product contains substances considered or proven to be carcinogenic. The carcinogenic effects may be triggered subsequent to exposure through inhalation, skin contact or ingestion. The product contains substances that cause serious eye damage. Contact with these substances can cause

irreversible effects on the eye / serious eye damage.

Other information

Silica-crystalline quartz has been classified by IARC as a group 1 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

No data available.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

- 12.4. Mobility in soil
- No data available.
- 12.5. Results of PBT and vPvB assessment
 - This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
- 12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations

RCRA Hazardous waste ("P" and "U" list) (40 CFR 261)

None of the components are listed

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1	14.2	14.3	14.4 14.5 Other
	UN / ID	UN proper shipping name	Hazard class(es)	PG* Env**information:
DOT	-	-	-	
IMDG	-	-	-	
IATA	-	-	-	

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to DOT, IATA and IMDG.

- 14.6. Special precautions for user
- Not applicable.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code No data available.

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012



Name of the product

Construction Quicklime

Revision Date: January 2025 Version: 2.0/EN

```
SECTION 15: Regulatory information
```

 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture 15.2. U.S. Federal regulations TSCA (the non-confidential portion)
Calcium oxide is listed Silica-crystalline quartz is listed
Clean Air Act
None of the components are listed
15.2. Safety health and environmental regulations/legislation encoding for the substance or mixture
15.3. Safety, health and environmental regulations/legislation specific for the substance or mixture 15.4. U.S. Federal regulations
TSCA (the non-confidential portion)
Calcium oxide is listed
Silica-crystalline quartz is listed
Clean Air Act
None of the components are listed
EPCRA Section 302 None of the components are listed
EPCRA Section 304
None of the components are listed
EPCRA section 313
None of the components are listed
CERCLA None of the components are listed
State regulations
California / Prop. 65
None of the components are listed
Massachusetts / Right To Know Act
Calcium oxide is listed
Silica-crystalline quartz is listed New Jersey / Right To Know Act
Calcium oxide / Substance number: 0325
Calcium oxide is on the Special Health Hazard Substance List
Silica-crystalline quartz is on the Special Health Hazard Substance List
_
New York / Right To Know Act
Calcium oxide is listed Calcium oxide is regulated with a Treshold Reporting Quantity (TRQ) of: 10 pounds
Pennsylvania / Right To Know Act
Calcium oxide is listed
15.4. Restrictions for application
Restricted to professional users.
Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical
precautions or design of the workplace needed to eliminate exposure, must be considered. 15.5. Demands for specific education
No specific requirements.
15.6. Additional information

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012



Name of the product

Construction Quicklime

Revision Date: January 2025 Version: 2.0/EN

Not applicable.

15.7. Chemical safety assessment

No

15.8. Sources

OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H315, Causes skin irritation.

H318, Causes serious eye damage.

H335, May cause respiratory irritation.

H350i, May cause cancer by inhalation.

H372, Causes damage to organs through prolonged or repeated exposure.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CERCLA = Comprehensive Environmental Response Compensation and Liability Act

DOT = Department of Transportation

EINECS = European Inventory of Existing Commercial chemical Substances

EPCRA = Emergency Planning and Community Right-To-Know Act

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HCIS = Hazardous Chemical Information System

HNOC = Hazards Not Otherwise Classified

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NFPA = National Fire Protection Association

NIOSH = National Institute for Occupational Safety and Health

OECD = Organisation for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

PBT = Persistent, Bioaccumulative and Toxic

RCRA = Resource Conservation and Recovery Act

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SARA = Superfund Amendments and Reauthorization Act

SCL = A specific concentration limit.

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TSCA = The Toxic Substances Control Act

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by HCS (29 CFR 1910.1200).

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012



Name of the product

Construction Quicklime

Revision Date: January 2025 Version: 2.0/EN

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: US-en

Disclaimer: The information contained herein is believed to be accurate and reliable as of the date hereof. However, Carmeuse makes no representation, warranty or guarantee as to results or as to the information's accuracy, reliability or completeness. Carmeuse has no liability for any loss or damage that may result from use of the information. Each user is responsible to review this information, satisfy itself as to the information's suitability and completeness, and the information to its employees, customers and other appropriate third parties.